



Product Highlights

- 50 Mbps symmetric throughput
- Native TDM transport
- Long range – up to 120 km/75 miles
- Advanced MIMO, OFDM and Diversity technologies
- Robust and reliable to operate in tough conditions, extreme temperatures and non line-of-sight scenarios
- Ease of operation and maintenance

RW-2960-0250

RW-2960-0250 is a carrier-class radio supporting the 6.0 GHz band.

The radio is part of the RADWIN 2000 L-Series which provides 50 Mbps symmetric throughput and a flexible combination of native TDM (up to 16 E1s/T1s) and Ethernet, enabling operators to cost-effectively support converged TDM and IP networks.

RADWIN RW-2960-0250 is connectorized for use with external antennas.

Product Specifications

Configuration	
Architecture	Outdoor Unit Connectorized for External Antenna
IDU to ODU Interface	Outdoor CAT-5e cable; Maximum cable length: 100 m
Radio	
Capacity	50 Mbps symmetric net throughput (up to 16 x E1s/T1s plus Ethernet)
Range	Up to 120 km / 75 miles
Channel Bandwidth	20 MHz
Modulation	2x2 MIMO-OFDM (BPSK/QPSK/16QAM/64QAM)
Adaptive Modulation & Coding	Supported
Automatic Channel Selection	Supported
Diversity	Supported
Spectrum View	Supported
Max Tx Power	20 dBm
Duplex Technology	TDD
Error Correction	FEC k = 1/2, 2/3, 3/4, 5/6
Encryption	AES 128
Supported Indoor Units	IDU-C Series (RW-72XX-2000)
Hub Site Synchronization (HSS)	Up to 16 collocated links (RADWIN 2000 and/or WinLink 1000)
Monitored Hot Standby (MHS)	1+1 with RADWIN 2000 link or WinLink 1000 link

Supported Bands		
Band	Occupied Frequency Range	Radio Compliance
6.0 GHz Universal	5.795 - 6.050	

Mechanical	
Dimensions	19.5(w) x 27.0(h) x 8.0(d) cm
Weight	1.8 kg / 3.6 lbs
Power	
Power Feeding	Power provided over ODU-IDU cable
Power Consumption	<35W (IDU + ODU)
Environmental	
Operating Temperatures	-35°C - 60°C / -31°F - 140°F
Humidity	100% condensing, IP67 (totally protected against dust and against immersion up to 1m)
Safety	
FCC/IC (cTUVus)	UL 60950-1, UL 60950-22, CAN/CSA C22.2 60950-1, CAN/CSA C22.2 60950-22
ETSI	EN/IEC 60950-1, EN/IEC 60950-22
EMC	
FCC	CFR47 Class B, Part15, Subpart B
ETSI	EN 300 386, EN 301 489-1, EN 301 489-4
CAN/CSA-CEI/IEC	CISPR 22-04 Class B
AS/NZS	CISPR 22-2004 Class B

Ordering Information

Part Number: RW-2960-0250

Description: RADWIN 2000 L-Series ODU Connectorized for external antenna (2x N-type), supporting 6.0 GHz band

For external antennas see the RADWIN Product Catalog.



Teleincom-PK
 Authorized Distributor and
 Service Center
 Russia & CIS
 T.: +7 (495) 231-21-20
 E.: info@teleincom.ru
 Web: www.radwin2000.ru